

# RLe Series

## Portable Rugged Label Printers ■ ■ ■



RL4e

RL3e

### features at a glance ■ ■ ■

- **Rugged and Reliable** - With uncompromising standards, the RLe Series endures even the most punishing environments, and passes the MIL-STD 810F drop-testing requirements. The RLe Series is so rugged it continues to print after 26 consecutive drops to concrete from six-feet (1.8m) even when tested at extreme temperature conditions.
- **Complete Line of Accessories** - The versatile RLe Series comes with a wide selection of charging and mounting accessories that allow it to be worn on the hip, mounted in a truck or even mounted and powered from a forklift.
- **Easy to Integrate** - The RLe Series comes with popular language emulations that allow you to easily replace existing printers in the workplace. The printer is also compatible with most popular WMS packages and offers optional wireless 802.11 and Bluetooth® connectivity.
- **Great Battery Power** - The long-lasting lithium-ion battery offers maximum power capacity for a full eight-hour shift, even under the toughest conditions.
- **Easy to Use** - Nobody likes to change the paper roll, but we've made it so easy you can do it with one hand. We've also included an easy-to-read LCD screen with simple user-interface buttons and a peel-and-present mechanism for quicker label application.
- **Complete Line of Media & Supplies** - Our Certified Label Supply Program ensures optimum, trouble-free performance from the RLe Series and guarantees the highest quality print output and image stability.
- **Two-Year Warranty** - Comes with the industry's only two-year standard warranty - twice that of the competition!

Datamax-O'Neil built its reputation on rugged and reliable portable receipt printers and has now used this expertise to design the industry's most rugged, portable label printer. The RL3e (3-inch/76mm) and RL4e (4-inch/102mm) are durable direct thermal printers with a rugged design and reliable performance that will continue to operate long after other printers have failed. We're so confident in the quality and long-term reliability of these printers that we include a two-year warranty free of charge. That's double what the competition offers.

Anybody who's ever been in a warehouse knows that when shipments are processed quickly and effectively, productivity is increased and errors are reduced. The RLe Series improves efficiency and productivity by allowing workers to print and apply barcode labels directly at the point of application. Using the RLe Series to print on-demand labels also eliminates the danger of mixing up batch-printed labels and saving thousands of dollars in potential shipping errors. The printer can even be mounted on forklifts for added convenience and versatility.

We've made integration easy. Replace existing printers using Datamax-O'Neil's language emulations. The RLe Series is compatible with most popular warehouse-management software programs, independent label-design programs and remote-management packages.

### popular applications ■ ■ ■



#### Logistics and Distribution

- Inventory Labels
- Content ID Labels
- Receiving Labels
- Shipping Labels



#### Parcel

- Shipping Labels
- Cross-Docking Labels
- Bin Labeling
- Stop Location Labels



#### Manufacturing

- Work in Process Labels
- Receiving and Location Labels
- Content ID Labels
- Shipping Labels



#### Retail

- Item Labels
- Shelf Tags
- Specials and Talkers
- Returns Labeling and Tagging

### your benefits ■ ■ ■

#### Increase Efficiency & Reduce Errors -

In many warehouses, workers travel to and from a central location to pick up "batch-printed" labels. While this method works, it also creates wasted movement and potential labeling errors. The RLe Series eliminates the danger of "label mix up" by printing labels at the point of application. And, since workers aren't wasting time traveling to a central location, warehouse operations are far more efficient and productive.

**Increase Productivity** - The RLe Series is built to keep pace in a busy warehouse. Labels print quickly and accurately every time, even in cold environments. Downtime is reduced thanks to a large media roll capacity and a battery that stays charged for a full shift.

**Enjoy Higher ROI** - In today's tough economic times, you can't afford to buy printers that fail. The RLe Series comes with Datamax-O'Neil's legendary reliability and is backed by the industry's only standard two-year warranty.



#### Did you know?

Using quality labels and paper can significantly prolong the life of your printhead. Datamax-O'Neil offers a wide variety of high-quality media for its printers including custom and stock labels and receipts, ticketing media, and cleaning products. When you choose Datamax-O'Neil, you receive a proven commitment to superior quality. Quality that results in performance and compatibility... Guaranteed.



datamax·oneil

by Honeywell

## ROI of Ultra-Rugged

Ultra-rugged products are often overlooked because of the purchase price, but many studies have shown the cost of implementing lower-cost hardware for professional use, especially in applications where products may be dropped or bumped frequently, is much greater than the cost of purchasing ultra-rugged equipment. RLe Series printers embrace abuse. They take the punishment outlined in the MIL-STD 810F standards, and continue to operate flawlessly even after being dropped multiple times from a height of six-feet (1.8m) onto concrete.

**1** Dual-wall construction and rubber bumpers protect critical printhead and platen roller alignment by absorbing and displacing energy when the printer is dropped or bumped.

**2** Die-cast magnesium bracket, large stainless-steel hinge pin and large gears further protect the platen roller.

**3** Unlike plastic or thin metal that breaks/bends easily when dropped, die-cast magnesium latches provide the perfect weight-to-strength ratio. Latches are lightweight yet rugged enough to endure repeated use and repeated six-foot (1.8m) drops to concrete.

**4** Robust media arms are constructed using thick media posts that won't jam or snap off easily. Large screws and durable glides ensure that this moving part will continue to operate trouble-free for the life of the printer.

**5** Arched design with rubber housing protects the recessed LCD screen and buttons. Internal anti-shock and anti-dampening foam further protects the LCD device.



**6** Port covers are made of a durable, rubberized material to protect against external environmental agents when ports are not in use.

We've leveraged our historic knowledge of rugged, portable printers to ensure that the printer's circuit boards are well protected by the RLe Series' outer shell and isolated sub-structure.

## Testing

One of the reasons we are able to include our **two-year warranty** is because of our extensive engineering experience and rigorous testing.

### Dropped again and again...

The RLe Series was tested using military MIL-STD 810F testing procedures which require that the printer operate after being dropped on all corners, edges and faces for a total of 26 consecutive times. The RLe Series passed MIL-STD 810F testing from a height of six- feet (1.8m) onto solid concrete!

### Wear & Tear

Recessed latch and port covers were opened and closed 30,000 times during testing to ensure their integrity and long-term reliability.

### Environmental Temperature Testing

The RLe Series was put through exhaustive testing to ensure its flawless performance at extreme temperatures including the freezing environments common in cold storage applications.

# product specifications ■ ■ ■

## physical characteristics ■ ■ ■

- Dimensions:
  - **RL3e:** 5.6" w x 7.6" h x 3.2" d (142 x 193 x 81 mm)
  - **RL4e:** 6.5" w x 7.9" h x 3.2" d (166 x 200 x 81 mm)
- Weight (printer only):
  - **RL3e:** 1.95 lb. (0.88 kg)
  - **RL4e:** 2.16 lb. (0.98 kg)
- Drop specifications:
  - 6 ft. (1.8 m)
- User interface:
  - 128x64 LCD display with white LED backlighting
  - Four (4) button user interface

## user environment ■ ■ ■

- Operating temperature:
  - 4° to 122°F (-20° to 50°C)
- Storage temperatures:
  - 40° to 140°F (-40° to 60°C)
- Charging temperatures:
  - 41° to 104°F (5° to 40°C)
- Relative humidity range:
  - 10% RH to 90% RH non-condensing
- ESD protection:
  - 8kV Air/ 6kV Contact

## print technology ■ ■ ■

- Printhead:
  - Direct thermal
  - 203 dots per inch (8 dots per mm)
- Print width:
  - **RL3e:** 2.8" (72 mm)
  - **RL4e:** 4.125" (105 mm)
- Print mechanism speed:
  - Upt to 4" per second (102 mm per second)<sup>1</sup>

## memory ■ ■ ■

- 64MB RAM / 128MB Flash

## media ■ ■ ■

- Media type:
  - **RL3e:** 1.00"– 3.125" (26 – 79 mm)
  - **RL4e:** 2.00"– 4.12" (51 – 105 mm)
  - Lined and linerless\* labels with black mark or gap sensing
  - External fanfold or roll supply
- Maximum roll capacity:
  - 2.65" (67 mm) O.D.
  - 0.75" (19 mm) I.D. core
- Media thickness:
  - 2 mil to 6.5 mil
- For optimum print quality and printer performance, use Certified Datamax-O'Neil supplies.

\* for use in RLe Series printers equipped with linerless option only

## communication ■ ■ ■

- Serial:
  - RS232, up to 460.8 kbps
- USB:
  - 2.0 (full speed-12 mbps)

- Bluetooth®:
  - Bluetooth® 4.0 + LE Dual Radio Mode (Q2 2015)
  - Serial port profile
- Security Modes 1-4
- Encryption 1-3e
- Bluetooth® Smart Ready
- 802.11 a/b/g/n Option:
  - Network standard: IEEE 802.11 a/b/g/n and Bluetooth® with Dual Mode Radio
  - Wireless access modes: Infrastructure and ad-hoc
  - Security Protocols:

	WEP	WPA	WPA2
Modes		PSK/Enterprise	
Security/Encryption	64/128	TKIP/RC4	CCMP/AES
Authentication	LEAP, EAP-PEAP, EAP-FAST, EAP-TLS, EAP-TTLS, EAP-LEAP		

- Internet Protocols Supported: UDP/TCP, DHCP, BootP, FTP, FTPS, SFTP, TFTP, Telnet, LDP, SNMP
- Remote and Auto Update features Supported
- 802.11i

## power source ■ ■ ■

- Battery:
  - 14.8V Lithium-ion, 2200 mAh (33 W-h)
- DC inputs:
  - External DC jack, 11-15V, built-in spike and surge protection with Battery Management
  - External charge contacts, 11-15V, built-in spike and surge protection
- Recharging: 4 - 6 hours
- **RL4e** Endurance: Prints over 320 4"x6" (100x150mm) labels when operating 16 continuous hours on an 802.11 network
- **RL3e** Endurance; Prints over 850 3"x1" labels (76x152mm) when operating for 28 consecutive hours on an 802.11 network

## agency approvals ■ ■ ■

- FCC 15 Class B, EN55022 Class B, EN55024, IEC 60950-1 2<sup>nd</sup> edition, EAC - Customs Union, CCC, SRRC
- Safety: UL/cUL, CE.
- Contact your sales representative for a complete list of approvals.

## warranty ■ ■ ■

- Two years (including platen roller, printhead and installed options) when used with approved supplies
- Contact sales representative for extended warranty options

## barcodes/fonts/graphics ■ ■ ■

- Scalable Fonts:
  - CG Triumvirate™ Bold Condensed, CG Triumvirate & CG Times with Cyrillic, Greek, Arabic and Hebrew character support from Monotype Imaging
- Standard fonts:
  - 5.5CPI, 7.2CPI, 10.2 CPI, 10.7CPI, 18.5CPI, 20.4CPI, 22.6CPI, 34.0CPI, OCR-A, OCR-B (additional fonts available)

- Downloadable font types:
  - True Type, Bitmap
- Character sets:
  - Unicode/UTF8 support; 50 international symbol sets, Big 5, JIS and Shift JIS and more
- Optional characters:
  - Arabic, Greek, Hebrew, Unicode subset including Latin
  - Asian (including Big 5, Simplified Chinese, Kanji, Hangul and Shift JIS); additional international characters available
- Barcodes:
  - Linear: Codabar, Code 3 of 9, Code 93, Code 128, EAN-8, EAN13, Interleaved 2 of 5, HIBC, PLESSEY, MSI/Plessey, UCC/EAN-128, UPC-A, UPC-E, UPC 2 and 5 digit addendums, Postnet, Telepen, UPS MaxiCode, FIM, USD-8
  - 2D Symbolologies: PDF417, Aztec, QR Code, GS1, Datamatrix, TLC39, MicroPDF417
- Graphics:
  - Supports storage of graphics/logos in Flash memory and transient "print once" graphic

## software/firmware ■ ■ ■

- NETira™ Configuration Tool - complete printer set-up utility
- NETira™ MS - Menu Scripting
- Control Language Compatibility:
  - Ez-Print, DPL, ZPL II®, CPCL, IPL™, XML (limited)
- Device Management Compatibility:
  - NETira™ Remote Management: Monitor and manage printers
  - NETira MD: Mobile Device Management Utility for Smart Mobile Devices.
  - NETira™ Connector (CA): Access AirWatch® Mobile Device Management Console
  - Wavelink® Avalanche MC
- Network Compatibility
  - TCP-IP based networks
  - AS/400 (LPD) based networks
- Drivers:
  - Microsoft Windows® XP/Vista/7 & 8
- NETira™ LD – Label Design Software
- Label Design Software Compatibility:
  - BarTender®, Niceware/NiceLabel and others
- ERP Systems Compatibility:
  - SAP, Oracle
- Software development kit:
  - Android 2.1 and above , iOS 5,6, & 7
  - Microsoft Windows Desktop up to Windows 8, Windows 8 Store, Windows Mobile & Windows CE
  - C++, C Sharp, Java, Active X Control

## other tools ■ ■ ■

- Lua and JSON Scripting Language
- AirWatch® support

## options ■ ■ ■

- Linerless
- Single Bay Charger for use with external charge contacts
- Dual Battery Charger
- Configurable Multi-Bay Charger
- Multi Unit Charging Adaptor
- Cigarette Lighter Vehicle Charger
- IP-54 Environmental Case


<sup>1</sup> Speed rating under normal optimal operating conditions. Performance may vary based on temperature of operating environment and label file density.



RAM Mount Compatible Adaptor



Voltage Converter



Multiple Unit Charging Adaptor



Double Bay Battery Charger



Multi-Bay RLe Charger



Vehicle Power Cable Kit

**Included with each RLe Series printer:**

(1) battery and (1) swivel belt clip

**required** ■ ■ ■

<b>AC Adaptor</b>	AC Adaptor available with US, UK, Australian, Swiss or Euro plugs (sold separately)
-------------------	---

**recommended** ■ ■ ■

<b>Serial Cables</b>	DB9 F cables for connecting to a laptop or desktop computer
<b>USB Cable</b>	USB download cable (mini B to USB-A)
<b>Cleaning Cards &amp; Kits</b>	Use of cleaning cards is recommended to extend the life of the printhead (visit <a href="http://www.datamax-oneil.com/supplies">www.datamax-oneil.com/supplies</a> for more information)

**optional** ■ ■ ■

<b>RAM Mount™ Compatible Adaptor</b>	Keeps the printer secure yet easily accessible on a forklift. Includes adaptor plate and 1-1/2" ball. Other parts are available from RAM Mount.
<b>Voltage Converter</b>	12-60V DC/DC power adaptor
<b>Multiple Unit Charging Adaptor</b>	Allows you to charge four (4) RLe Series printers or four (4) two-bay battery chargers at once, requires a high-capacity AC Adaptor (included). Available in US, UK and Euro Plugs.
<b>Spare Battery</b>	Lithium-Ion, 14.8V, 2200 mAh
<b>Double Bay Battery Charger</b>	Two-bay battery charger keeps additional batteries charged and ready for use
<b>Multi-Bay RL Charger</b>	Configurable charging station capable of charging multiple units or combination of units and batteries. (Cables and high-capacity charger included).
<b>Vehicle Power Cable Kit, 10'</b>	Charge your printer from a vehicle's fuse box Extension cables available in 3', 6', and 10' lengths for existing installations
<b>IP54 Soft Case</b>	Protects your printer from environmental elements such as dust and moisture; meets IP54 test standards
<b>Cigarette Lighter Adaptor</b>	Allows you to charge the printer from the vehicle cigarette lighter. (Either 12v or 24v input models available).
<b>Swivel Mount Belt Loop</b>	Velcro® loop fastens comfortably and securely around the belt; keeps the printer secure yet swivels for comfort while bending over or getting in and out of vehicles
<b>Hand Strap &amp; Shoulder Strap</b>	Choose either a hand or shoulder strap for maximum comfort and flexibility



**Looking for a desktop label printer?**

Datamax-O'Neil manufactures an extensive selection of desktop label printers that are ideal for manufacturing, warehouse, healthcare, ticketing, postal services and RFID labeling requirements. Competitive custom and standard media products are also available for all your label, receipt and ticketing needs.



datamax·oneil  
by Honeywell



**to learn more, visit [www.datamax-oneil.com](http://www.datamax-oneil.com)**

©2015 Datamax-O'Neil - NETira™ is registered trademark of Datamax-O'Neil. All rights reserved.  
\*Bluetooth® is a registered trademark of Bluetooth SIG.  
Windows 8, Windows XP, and Windows CE are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.  
All other trademarks are the property of their respective owners.